PRODUCT CATALOGUE

Intrinsically Safe Ex-proof Portable Lighting Expert









Intrinsically Safe Ex-proof Torches

SCAN FOR MORE **PRODUCT FEATURES**





ExMP21R

| I, II Zone 1/2, Zone 21/22



Rechargeable li-ion battery



-40°C~+55°C



ExMP21N

| I, II Zone 0/1/2, Zone 21/22



Alkaline battery



-40°C~+55°C



ExMP31R



| I, II Zone 1/2, Zone 21/22



Rechargeable li-ion battery



-40°C~+55°C



Dual power supply



ExMP31N



| I, II Zone 0/1/2, Zone 21/22



Alkaline battery



-40°C~+55°C(T3)/50°C(T4)



Dual power supply



ExMP32R



| I, II Zone 1/2, Zone 21/22



Rechargeable li-ion battery



-40°C~+55°C



Dual light mode 90° Rotational head



ExMP32N



I, II Zone 0/1/2, Zone 21/22



Alkaline battery

Dual light mode



-40°C~+55°C(T3)/50°C(T4)



90° Rotational head



Intrinsically Safe Ex-proof Handlamps

SCAN FOR MORE PRODUCT FEATURES





ExMP51R

- | II Zone 1/2, Zone 21/22
- Rechargeable li-ion battery
- -20°C~+55°C
- 4 colors light source
- 90° Rotational head



ExMP52R

- | Il Zone 1/2, Zone 21/22
- Rechargeable li-ion battery
- -40°C~+55°C
- ☐: Head & tail lights
- Optional indicator color
 - 180° Rotational head



Intrinsically Safe Ex-proof Headtorches

SCAN FOR MORE PRODUCT FEATURES





ExMP61R-1

-] I, II Zone 0/1/2, Zone 21/22
- Rechargeable li-ion battery
- -40°C~+55°C
- 108° Rotational head





ExMP61R-2

- | Il Zone 0/1/2, Zone 21/22
- Rechargeable li-ion battery
- -40°C~+55°C
 - 108° Rotational head





Ex-proof Light Towers

SCAN FOR MORE PRODUCT FEATURES







Industrial Product Series

SCAN FOR MORE PRODUCT FEATURES

(€





Integrated Charging System

SCAN FOR MORE PRODUCT FEATURES

((





High Performance Nylon



Latest International Ex-poof Standards and Regulations 3

Integrated Charging System





4

Constant Current Source Design



Modular Design



Comprehensive Lifecycle Management











SAFELY LIGHTEN EACH AND EVERY DAY

