

Weatherproof Telephone ResistTel

Comfortable telephone for rough environmental conditions



Overview

ResistTel stands for: telephony under rough environmental conditions with the highest degree of safety in industrial areas.

Our telephone is resistant to seawater as well as alkali, acids and lubricants.

The housing made of special compression-moulded material is impact-resistant. The stainless steel keypad withstands high stresses and protects the inner parts of the telephone. The steel-armoured handset cord is designed for high tensile strain.

Its alphanumeric display allows for a clear reading. Moreover, the telephone offers all the amenities that are already supplied as standard in the office communication sector. A number of accessories and components even enhance the telephone's functionality.

Features

- Locking function with PIN
- Hands-free operation
- Temperature range -25 °C to +60 °C
- Display
- IP 66 according to EN 60529
- Different housing colours

EATON




Powering Business Worldwide



General arrangement drawing (all dimensions in mm)

Specifications

Supply voltage	24 VDC to 66 VDC
Supply current	15 mA to 100 mA
Ringing alternating current	24 VAC to 90 VAC (at 21 to 54 Hz ringing frequency) 30 VAC to 90 VAC (at 16.6 ... 54 Hz ringing frequency)
Ring tone impedance	Greater than 6.0 kΩ at 25 Hz and 24 to 90 VAC. Greater than 4.0 kΩ at 50 Hz and 24 to 90 VAC
Inquiry key	Flash function may be set from 40 ms to 399 ms
Dialling procedure	PD-DTMF operation to be set in the menu. PD operation where the pulse/pause ratio can be set to 1.5:1 or 2:1 in the menu
W-conductor	Connection for external secondary sounder
Connection terminals	Up to 4 mm ² rigid, Up to 2.5 mm ² flexible
Housing Material	Glass fibre reinforced polyester
Height x width x depth	Approx. 266 mm x 227 mm x 135 mm
Weight	Approx. 5.5 kg
Display	Two-line alphanumeric display with pictograms Visual field approx. 78 mm x 26 mm
Keypad	Metal keypad with ice protection 21 keys with ABC lettering for name entries
Receiver	
Stabilization bracket	Integrated adjustable stabilization bracket
Handset cord	Stainless steel armoured cord
Earpiece	Dynamic capsule with stray field coil for inductive coupling of hearing aids
Mouthpiece	Electret microphone
Noise suppression	Greater than 3 dB due to integrated horn mouth
Environmental conditions	
Ingress protection	IP 66 according to EN60529
Impact protection	IK 09 according to EN50102
Operating temperature	-25 °C to +60 °C
Storage temperature	-25 °C to +70 °C
Optical call indication	Display screen (((🔔)))
Ringing volume	Approx. 95 dB(A) in 1 m distance
Ring tones	10 sounds available
Listening by loudspeaker	Maximum volume approx. 68 dB(A) in 1 m distance
Handsfree	Maximum volume approx. 68 dB(A) in 1 m distance
Amplified listening	Receiver volume may be set from 0 dB(A) to +12 dB(A), in 7 steps
Menu guide	Multilingual
Telephone book	Max. 50 items (names and phone numbers)



Accessories



Headset



Additional earpiece



Loudspeaker set



TWIN



Protection hood



Secondary sounder

Ordering data

* The full article number for the TWIN is made up by appending the colour code to the article numbers given below.

Type	Designation	Model	Article number		
ResistTel	Weatherproof Telephone	black	FHF 112 643 01	transparent	01
ResistTel	Weatherproof Telephone	red	FHF 112 643 01 02	red	02
ResistTel	Weatherproof Telephone ZB	black	FHF 112 643 02	amber	03
ResistTel	Weatherproof Telephone ZB	red	FHF 112 643 02 02	green	04
				blue	05

Accessories

	Additional Earpiece		FHF 112 643 03
	Headset		FHF 112 643 04
	Loudspeaker Set		FHF 112 643 05
	Secondary Sounder		FHF 211 101 05
	TWIN		FHF 118 832 ..*
	Telephone Hood Model 404	galvanized steel, yellow	FHF 118 901 01
	Telephone Hood Model 404	stainless steel	FHF 118 901 11
	Telephone Hood Model 404	synthetic material, orange	FHF 118 901 12
	Telephone Hood Model 404	synthetic material, yellow	FHF 118 901 13
	Telephone Hood Model 404	galvanized steel, red	FHF 118 901 14
	Telephone Hood Model 404	synthetic material, red	FHF 118 901 15
	Telephone Hood Model 404	GRP, yellow	FHF 118 901 22
	Telephone Hood Model 404	GRP, orange	FHF 118 901 23
	Floor mounting console for Model 404	yellow	FHF 118 901 03

Accessories are not available as DNV variants.